

**FRITZ BRUNNHOFER GMBH
HAIMENDORFER STRASSE 57 90571 ,
SCHWAIG/NUREMBERG FED REP GERMANY**

MH15581 (N)

(A card)

Pressure-sensitive systems:

"SC3690ED FB3M", "SC3698ED FB3M", "SC3690-523ED FB3M", "SC3690E FB3M" or "SC3698E FB3M", removable intact. Affixed to aluminum, alkyd enamel, zinc, zinc plated metal with chromate post treatment, polyurethane paint and polyester paint, maximum temperature 100 C (212 F), minimum temperature -40 C (-40 F); stainless steel, galvanized steel and polypropylene, maximum temperature 80 C (176 F), minimum temperature -40 C (-40 F); acrylic lacquer, polycarbonate, polyphenylene oxide (PPOX) plastic, nylon plastic and acrylonitrile butadiene styrene (ABS) plastic, maximum temperature 60 C (140 F), minimum temperature -40 C (-40 F). Suitable where exposed indoors and outdoors to high humidity or occasional exposure to water or lubricating oil. Suitable for additional printing using certain ribbon inks except "SC3690E FB3M", "SC3698E FB3M".

"SC3650 FB3M", "SC3658 FB3M", removable intact. Affixed to alkyd enamel, acrylic lacquer and stainless steel, maximum temperature 100 C (212 F), minimum temperature -40 C (-40 F). Suitable where exposed indoors or outdoors to high humidity or occasional exposure to water or oils.

Reports: **September 22, 1987; September 23, 1987.**

Replaces MH15581A dated October 31, 1991.

(Cont. on B card)